

MODEL ZW205 - Pressure Relief / Pressure Sustaining Valve Control Valve Order Form



Customer: _____ Date: _____
 Contact: _____ Email: _____
 Telephone/Fax: _____ Ref. P. O. _____

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee.
 Contact Customer Care for details on return policies.

Size: (Check one) 1-1/4" 1-1/2" 2" 2-1/2" 3" 4" 6" 8" 10"

Body: Globe

Valve body is ductile iron, epoxy coated

Function Options:

- Check all that apply
- Isolation Valves, Inlet Pressure Gauge, and "Wye" Type Strainer
 - "C" Option * - Check Valve with Isolation Valve
 - "L" Option * - Closing Speed Control
(Standard on 4" or smaller)
 - "O" Option * - Opening Speed Control



End Connections:

- Check one
- ANSI Class 150 Flanges (1-1/2" - 10")
 - "G" Option - IPS Grooved (1-1/2" - 10")
 - "TH" Option - NPT Threaded (1-1/4" - 3")
 - "Y" Option * - ANSI Class 300 Flanges (1-1/2" - 10")

Main Valve Options:

- Check one
- Bronze Seat, Seal Ring Retainer, and Stem Guide
 - "SS" Option * - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide

- Check all that apply
- "Z" Option * - Visual Position Indicator

Pilot Options:

- Check one
- Pressure Relief Pilot (50 - 200 psi)
 - "HP" Option* - PV-RLF Pilot (150-300 psi)
 - "LP" Option* - PV-RLF Pilot (30-90 psi)
 - "LP2" Option* - PV-RLF Pilot (10-35 psi)
 - "LP3" Option* - PV-RLF Pilot (5-15 psi)

- Check one
- Copper Tubing and Brass Fittings
 - "ST" Option * - Stainless Steel Tubing and Fittings

- Check all that apply
- "RV" Option - Pilot Installed on Reverse Side
 - "GL" Option * - Liquid Filled Gauge

*Adder to standard price applies

1747 Commerce Way
 Paso Robles, CA 93446
 Phone: 877-222-5356
 Fax: 805-237-7197

Customer Service Representatives available
 Monday through Friday 5:30 a.m. to 5:00 p.m., PST
 Fax completed forms to 805-237-7197, attention: Sales
 Call 877-222-5356, wilkinscs@zurnwilkins.com
 or visit us online at www.zurn.com

