

Location: \_\_\_\_\_




## F1170-C-SD

**FLOOR DRAIN WITH MULTI INLETS AND INTEGRAL TRAP AND SQUARE SOLID HINGED COVER FOR MEMBRANE FLOOR AREAS**

**Specification:** MIFAB Series F1170-C-SD lacquered cast iron floor drain with integral trap, 2" (51) cleanout (rodding eye), anchor flange, cast iron membrane clamp ring with primary and secondary weepholes for waterproofing membrane, and adjustable "SD6" square 6" x 6" (152 x 152) with solid hinged cover and secondary grate. (Specify -44, 2" (51) no hub inlets as shown and required. Maximum three @ 90 degrees. Specify location -A, B, or C.)


**Function:** Used in toilets, kitchens and other membrane finished areas where additional inlets are required to receive drainage. Integral deep seal trap prevents sewer gas from entering area.



### PARTS:



F117(\*)  
(\*) Denotes Outlet Size



(\*)-(\*\*)  
(\*) Denotes Strainer Diameter (5", 6", 7", 8" or 10")  
(\*\*) Denotes Strainer Finish (-1, -3 or -4)



A1-C1



HS-1

F1170-C-SD Series meets  
ANSI-ASME floor  
drain standard  
A112.6.3-2001

STRAINER DIAMETER	STRAINER ADJUSTMENT		ANSI/ASME RATING			PIPE SIZE	BODY HEIGHT	
			FREE AREA	LOAD RATING			A	B
	MIN	MAX		N.B. (-1)	S.S. (-3)			
6" x 6" (152 x 152)	2" (51)	3 1/8" (79)	12 in² (7700²)	UP TO 2,000 LBS.	5000-7499 LBS.	3" (76) 4" (102)	3 3/4" (95) 3 3/4" (95)	7 7/8" (200) 7 7/8" (200)

#### SUFFIX OPTIONAL VARIATIONS

- 1 Nickel bronze strainer
- 3 Stainless steel strainer
- 4 Ductile iron grate (5" x 8" only)
- 5 Sediment bucket
- 6 Security screws (T-20 Torx & pin)
- 7 1/2" trap seal primer connection
- 8 Backwater valve (2", 3", 4")
- 11 Acid resistant epoxy coated body
- 13 Galvanized body
- 15 Extension

#### SUFFIX OPTIONAL VARIATIONS

- 34 Closure plug
- 44 2" (51) no hub inlet (specify A, B, C locations)
- 49 Chrome Plated Strainer
- 95 Client logo
- ARRA ARRA (Stimulus Act) compliant product
- BA Buy American Act compliant product

#### SUFFIX OPTIONAL VARIATIONS

- C2 High rough-in membrane clamp (min. 1 9/16" (40))
- HP Heel proof grate (1/4" maximum grate opening size, -3 only)
- PA Pennsylvania Steel Act compliant product
- Z Extended wide elastomeric flange

Job Name: \_\_\_\_\_  
Section No: \_\_\_\_\_  
Schedule No: \_\_\_\_\_

Page No: \_\_\_\_\_  
Contract: \_\_\_\_\_  
Purchase Order No: \_\_\_\_\_