

Location: \_\_\_\_\_



**MHY-61**

**LAWN/GROUND HYDRANT  
1 1/4", 1 1/2", 2" CONNECTION**

**Specification:** MIFAB Series MHY-61 \_\_\_\_ (specify length) A.S.S.E. 1019-B certified self draining, non freeze, lawn/ground hydrant with A.S.S.E. 1011 approved anti-siphon and vandal resistant integral vacuum breaker with 3/4" (19) male hose connection. Hydrant assembly complete with one piece neoprene plunger to control both the flow and drain functions, hardened bronze operating stem, drain port under the hexagon nut, heavy duty galvanized steel pipe, heavy duty chrome plated bronze head casting, polished chrome plated face plate and satin finished nickel bronze box with hinged locking cover. Operating key furnished with each hydrant opens the hydrant, box and prevents unauthorized use. Hydrant inlet connection complete with drain port tapped for 1/8" (3) N.P.T.

**Function:** Lawn/ground hydrants are installed flush with surrounding surfaces and are intended for use on golf courses, shopping centers, parks and landscaped areas around buildings. Suitable for connection to 1 1/4", 1 1/2" or 2" water supply.

Plumbing and Drainage  
Mechanical Section

**SATIN FINISHED NICKEL BRONZE  
BOX WITH HINGED LOCKING COVER**




**3/4" (19) MALE HOSE  
CONNECTION**

**POLISHED CHROME PLATED FACE  
PLATE**

**DRAIN PORT TAPPED FOR 1/8" (3) NPT**


**1 1/4", 1 1/2" OR 2" MALE  
THREADED INLET  
CONNECTION  
RECOMMENDED OPENING  
5 1/4" (133) X 6 1/4" (158)**



**HEAVY DUTY  
GALVANIZED  
STEEL PIPE**

**(DIMENSION)  
DENOTES  
MILLIMETERS**

Side view



#### MHY-60 Series Features

- **INTERNAL COMPONENTS** - hardened bronze operating stem and one piece neoprene plunger.
- **VACUUM BREAKER** - unique self draining vandal resistant integral vacuum breaker protects from anti-siphon conditions.
- **CASING** - heavy duty galvanized steel pipe.
- **APPROVALS** - MHY60 Series wall hydrant is tested and certified to the A.S.S.E. Standard 1019-B and listed by I.A.F.M.O. The anti-siphon vacuum breaker is tested and certified to the A.S.S.E. Standard 1011 and listed by I.A.F.M.O.



MODEL NO.	BURY DEPTH		INLET CONNECTION
	FT	MM	
MHY-61-2	2	603	1 1/4", 1 1/2" or 2" M.I.P.
MHY-61-3	3	905	1 1/4", 1 1/2" or 2" M.I.P.
MHY-61-4	4	1207	1 1/4", 1 1/2" or 2" M.I.P.
MHY-61-5	5	1508	1 1/4", 1 1/2" or 2" M.I.P.
MHY-61-6	6	1810	1 1/4", 1 1/2" or 2" M.I.P.
MHY-61-7	7	2112	1 1/4", 1 1/2" or 2" M.I.P.
MHY-61-8	8	2414	1 1/4", 1 1/2" or 2" M.I.P.

#### SUFFIX OPTIONAL VARIATIONS:

- 0 1" (25) Hose connection
- 3 Cast stainless steel hydrant box
- 9 1/4" (6) drain port in box
- 10 3/8" (9) drain port in box
- 11 1/2" (13) drain port in box
- 49 Polished chrome plated nickel bronze box

#### SUFFIX

- 125 1 1/4" connection
- 150 1 1/2" connection
- 200 2" connection
- BA Buy American Act compliant product
- FL Anchor flange
- FLM Anchor flange and membrane clamp
- HSB Hose storage box (cast iron)
- K Cylinder key lock

(Dimension) Denotes Millimetres

Job Name: \_\_\_\_\_  
Section No: \_\_\_\_\_  
Schedule No: \_\_\_\_\_

Page No: \_\_\_\_\_  
Contractor: \_\_\_\_\_  
Purchase Order No: \_\_\_\_\_

MIFAB reserves the right to make changes in material and design without formal notice and obligation.

USA: 1-800-465-2736 www.mifab.com CAN: 1-800-387-3880