Location:

Plumbing and Drainage



POST HYDRANT

Specification: MIFAB Series MHY-65 _____ (specify length) non freeze post hydrant with exposed bronze head and combination 3/4" (19) female and 1" (25) male inlet connection. Hydrant assembly complete with one piece neoprene plunger, hardened bronze operating stem, 1" (25) galvanized steel casing, heavy duty bronze head casting with head nut assembly, 3/8" (9) diameter galvanized steel operating rod, decorative casing guard, tapped 1/8" (3) drain port in the bronze tailpiece, and an operating key.

MHY-65

OPERATING KEY HANDLE DECORATIVE prevent freezing. **CASING GUARD 4**" (102)(OPTIONAL) to internal parts. 3/4" (19) MALE HOSE CONNECTION Mechanical Section HEAVY DUTY 24" 20" **BRONZE HEAD** (610)(508)CASTING (25) GALVANIZED STEEL CASING **GROUND LEVEL** -0 -8 -12 -42 **BURY DEPTH DRAIN PORT** TAPPED FOR 1/8" (3) N.PT. **COMBINATION 3/4**" (19) FEMALE OR 1" (25) MALE THREADED INLET CONNECTION

Operation: Opening the hydrant will allow water to flow freely from the hose connection and seal the drain port to prevent water from being wasted. Closing the hydrant opens the drain port to allow existing water in the hydrant to drain to prevent freezing.

Features: The 1" (25) galvanized steel casing will prevent rust and deterioration in acidic ground areas. The head nut assembly can be removed for ready access to internal parts.

Function: Intended for installation in exterior deck areas, farms, golf courses, parks, recreation and landscaped areas to provide a ready supply of potable water.

MODEL NO.	OVERALL LENGTH IN MM		BURY DEPTH FT CM		APPROXIMATE WEIGHT Lbs. Kg.	
MHY-65-2	48	122.0	2	60.9	10	4.53
MHY-65-3	60	152.0	3	91.4	13	5.89
MHY-65-4	72	183.0	4	121.9	15	6.80
MHY-65-5	84	213.0	5	155.4	17	7.71
MHY-65-6	96	244.0	6	182.9	19	8.61
MHY-65-7	108	274.0	7	213.4	21	9.52
MHY-65-8	120	305.0	8	243.8	23	10.43
MHY-65-9	132	355.0	9	274.3	25	11.34
MHY-65-10	144	366.0	10	304.8	27	12.24

SUFFIX OPTIONAL VARIATIONS:

- -0 1" (25) hose connection
- -8 Vacuum breaker
 - (Certified to A.S.S.E. Standard 1011 and listed with I.A.P.M.O.)
- -12 Wheel handle
- -42 Decorative casing guard

(Dimension) Denotes Millimetres

	Job Name:	Page No:
	Section No:	Contractor:
	Schedule No:	Purchase Order No:
MIFAB reserves the right to make changes in material and design without formal notice and obligation.		USA: 1-800-465-2736 www.mifab.com CAN: 1-800-387-3880