



ACCESSORIES

Leonard's complete line of shower and bath accessories complements our thermostatic and pressure-actuated mixing valves for commercial/institutional installations.

SHOWER HEADS

HAND SHOWERS

DIVERTER VALVES

ON/OFF AND METERING VALVES

TUB AND DIVERTER SPOUTS

VACUUM BREAKERS

DIAL THERMOMETERS

REMODEL PLATES

SHOWER HEADS

All shower heads are polished chrome-plated and include a shower arm and flange



H-01 shower head, brass, ball joint, volume control, 2.5 GPM (9.5 l/min)



H-02 shower head, brass, ball joint, adjustable spray, 2.5 GPM (9.5 l/min)



H-03 large shower head, brass, ball joint, adjustable spray, 2.5 GPM (9.5 l/min)



H-05 shower head, ABS, ball joint, adjustable spray, 2.5 GPM (9.5 l/min)



C10-2S shower head, brass, ball joint, 2.0 GPM (7.6 l/min)



H-14 Low Flow shower head, ABS, ball joint, 1.5 GPM (5.7 l/min)

Options: Suffix V Separate volume control, lever adjustment

Suffix CFL Cast flange with set screw

INSTITUTIONAL SHOWER HEADS

All institutional shower heads are polished chrome-plated and mounted on an institutional shower head bracket



H-06 institutional shower head, brass, vandal-resistant screws, 2.5 GPM (9.5 l/min)



H-06-1.5GPM institutional shower head, brass, vandal-resistant screws, 1.5 GPM (5.7 l/min)



H-06-ADJ institutional shower head, brass, adjustable spray with lockable setting, vandal-resistant screws, 2.5 GPM (9.5 l/min)



H-06-C10-2S institutional shower head, brass, ball joint, vandal-resistant screws, 2.0 GPM (7.6 l/min)



H-07 institutional shower head, large size, brass, ball joint, adjustable spray, vandal-resistant screws, 2.5 GPM (9.5 l/min)



H-08 institutional shower head, brass, ball joint, adjustable spray, vandal-resistant screws, 2.5 GPM (9.5 l/min)



H-09 institutional shower head, ABS, ball joint, adjustable spray, vandal-resistant screws, 2.5 GPM (9.5 l/min)



H-10 institutional shower head, brass, ball joint, volume control, vandal-resistant screws, 2.5 GPM (9.5 l/min)



H-15 Low Flow institutional shower head, brass ball joint, vandal resistant screws, 1.5 GPM (5.7 l/min)

DIVERTER SPOUTS, TUB SPOUTS

All diverter and tub spouts are chrome-plated

D diverter spout

D-1 diverter spout, twin elbow



TS tub spout



DIVERTER VALVES

D-2L inline diverter valve, brass lever handle, 1/2" copper tube connections

D-2 inline diverter valve, die cast handle, 1/2" copper tube connections

L-4923 shower head diverter, chrome-plated finish



Options: Suffix Br Brass construction (D, D-1, TS)

HAND SHOWERS

All hand showers include spray, 2.5 GPM (9.5 l/min) flow rate, 69" (1753 mm) chrome hose, inline vacuum breaker, supply elbow and flange



500P with two wall hooks



501P with 24" (610mm) slide bar



501P(G) with 24" (610mm) glide rail



501P(G)-30 with 30" (762mm) glide rail



503P with 44" (1117mm) slide bar



62001 ADA-compliant hand shower with 24" grab bar



62003 ADA-compliant hand shower with 36" grab bar
62001 & 62003 not available in 1.5 GPM



Options:

Suffix ADJ Deluxe adjustable spray head

Suffix RV Reinforced vinyl hose

Suffix QD Quick connector fitting

Suffix 505P Same as 500P, except 1.5 GPM hand shower

Suffix 515P Same as 501P, except 1.5 GPM hand shower

Suffix 515P(G) Same as 501P(G), except 1.5 GPM hand shower

Suffix 515P(G)-30 Same as 501P(G)-30, except 1.5 GPM hand shower

ON/OFF VALVES, METERING VALVE



770 compression-type volume/on/off valve, four-arm handle, exposed parts chrome-plated, 1/2" IPS connections



770-BL compression-type volume/on/off valve, blade handle



LV477B-3 metering valve, concealed, pushbutton activation, fixed cycle, 30 seconds, inlet stop, exposed parts chrome-plated, 1/2" IPS connections

DIAL THERMOMETERS



37C30A range: 0-140°F, -20-60°C, 15/16" bulb, 3 color, 3-1/2" dial, bimetal type



37C20A range: 20-240°F, 5-115°C, 1.12" bulb, 3-1/2" black dial, bimetal type



2122 FOR TEPID APPLICATIONS range: 0-140°F, -20-60°C, 15/16" bulb, special 4 color, 3-1/2" dial, bimetal type



37C50FL flush mounted, range: 25-125°F, 0-50°C, with wall flange, mounting bracket and screws

INSTITUTIONAL SPRAYS

All institutional sprays include 6 ft. (1828mm) black rubber hose and wall hook



5P plain (open) end hose



5RS rose spray



5SCRS self-closing rose spray

VACUUM BREAKERS



LVB elevated vacuum breaker, chrome-plated, 1/2" with hose connection on outlet



EVB elevated vacuum breaker unit, chrome-plated, 1/2" IPS



INVB inline vacuum breaker (included on Hand Shower units)

REMODEL PLATE



02000 remodel plate, stainless steel, #4 finish for 4500 or PAM-II-ST shower valves



7929 remodel plate, stainless steel, #4 finish for 7600 shower valve

Note: All specifications are subject to change without notice!



1360 Elmwood Avenue
Cranston, RI 02910 USA
800.222.1208
t 401.461.1200
f 401.941.5310
info@leonardvalve.com
www.leonardvalve.com

LV-113 03/10
Printed in the U.S.A.

©Leonard Valve Company 2010