



Swan Wax with Urethane

Products - [Cat 4 - Wax Gaskets, Cold Solders, and Lubricants](#)



DESCRIPTION

Black Swan's Swan Wax with Urethane is a urethane gasket made of a tough, flexible and durable urethane foam. This urethane gasket is then impregnated with wax. The combination of the urethane foam and the wax makes for a stronger, more resilient ring than regular rings and is guaranteed for 10 years. Can be used for setting all floor outlet toilet bowls. The gasket forms a water tight, gas tight and odor tight seal. Fits 3" and 4" waste lines. Meets Federal Specification TT-P-1536A.

DIRECTIONS

1. Be sure the wax ring is at room temperature (about 70°F). If wax ring is too cold a good seal may not be made or the toilet bowl could crack while making the installation.
2. With the toilet bowl upside down on a protective pad or blanket, place the wax ring around the discharge opening. Press firmly to assure adhesion when toilet is inverted.
3. Using **Black Swan's Stainless or Stay Soft Putty** make a putty ring about 1 inch high around the outside rim of the toilet. This will make a seal between the toilet rim and the floor.
4. Carefully set toilet down in bolts and twist bowl slightly to spread wax and putty to make a tight seal. Tighten bolts carefully to prevent breaking the bowl.

UPC NUMBER AND CARTON INFORMATION

<u>STOCK NO.</u>	<u>SIZE</u>	<u>UPC NUMBER</u>	<u>CARTON CUBIC FEET</u>
04003	-	0 54647 0 04003 5	1.37
MSDS			
Buy Now			

