

Flange & Gasket with Brass Bolt Kit

Products - Cat 4 - Wax Gaskets, Cold Solders, and Lubricants



DESCRIPTION

**Black Swan's Flange & Gasket with Brass Bolt Kit** is a 100% pure wax gasket for setting all floor outlet toilet bowls. This ring has a plastic flange which extends the discharge opening. This makes for a more positive seal and assures proper bowl alignment. The gasket forms a water tight, gas tight and odor tight seal. Fits 3" and 4" waste lines. Includes two 1/4" X 2-1/4" brass bolts, two nuts, two washers, and two plastic stand-up washers. Meets Federal Specification TT-P-1536A. For certain locations throughout the United States local codes require the plastic flange to fit 4" openings only. Black Swan does have this product available (Stock No. 4011).

DIRECTIONS

1. Be sure the wax ring is at room temperature (about 70°F). If wax ring is too cold a good seal may not be a made or the toilet bowl could crack while making the installation.
2. With the toilet bowl upside down on a protective pad or blanket, place the wax ring around the discharge opening, extending plastic flange away from the bowl. Press firmly to assure adhesion when the toilet is inverted.
3. Using **Black Swan's Stainless or Stay Soft Putty** make a putty ring about 1 inch high around the outside rim of the toilet. This will make a seal between the toilet rim and the floor.
4. Carefully set toilet down on bolts and twist bowl slightly to spread wax and putty to make a tight seal. Tighten bolts carefully to prevent breaking the bowl.

ACCESSORIES

Includes two 1/4" X 2-1/4" brass bolts, two nuts, two washers, and two plastic stand-up washers

STOCK NO.	SIZE	UPC NUMBER	CARTON CUBIC FEET
04006	--	0 54647 04006 6	1.37
MSDS			

[Buy Now](#)