



Flange & Gasket with Urethane

Products - [Cat 4 - Wax Gaskets, Cold Solders, and Lubricants](#)



DESCRIPTION

Black Swan's Flange & Gasket with Urethane is a urethane gasket made of a tough, flexible and durable urethane foam. This urethane gasket is then impregnated with wax. The combination of urethane foam and the wax makes for a stronger, more resilient ring than regular rings and is guaranteed for 10 years. Can be used for setting all floor outlet toilet bowls. The gasket forms a water tight, gas tight and odor tight seal. Fits 3" and 4" waste lines. Meets Federal Specification TT-P-1536A. This ring has a plastic flange which extends the discharge opening. This makes for a more positive seal and assures proper bowl alignment.

DIRECTIONS

1. Be sure the wax ring is at room temperature (about 70°F). If wax ring is too cold a good seal may not be made or the toilet bowl could crack while making the installation.
2. With the toilet bowl upside down on a protective pad or blanket, place the wax ring around the discharge opening, extending plastic flange away from the bowl. Press firmly to assure adhesion when the toilet is inverted.
3. Using **Black Swan's Stainless or Stay Soft Putty** make a putty ring about 1 inch high around the outside rim of the toilet. This will make a seal between the toilet rim and the floor.
4. Carefully set toilet down on bolts and twist bowl slightly to spread wax and putty to make a tight seal. Tighten bolts carefully to prevent breaking the bowl.

UPC NUMBER AND CARTON INFORMATION

STOCK NO.	SIZE	UPC NUMBER	CARTON CUBIC FEET
04008	--	0 54647 04008 0	1.37
MSDS			
Buy Now			

