

Accessories



Leonard's Complete Line of Shower and Bath Accessories Complements Our Thermostatic and Pressure-Actuated Mixing Valves



Shower Heads
Hand Showers
Diverter Valves
Volume Control and Metering Valves
Tub and Diverter Spouts
Vacuum Breakers
Dial Thermometers
Remodel Plates



For commercial and institutional installations.



Accessories

Shower Heads

All shower heads are polished chrome-plated and include a shower arm and flange

H-01 shower head, brass, ball joint, volume control, 2.5 GPM (9.5 l/min)



H-02 shower head, brass, ball joint, adjustable spray, 2.5 GPM (9.5 l/min)



H-03 large shower head, brass, ball joint, adjustable spray, 2.5 GPM (9.5 l/min)



H-05 shower head, ABS, ball joint, adjustable spray, 2.5 GPM (9.5 l/min)



C10-2S shower head, brass, ball joint, 2.0 GPM (7.6 l/min)



H-14 Low Flow shower head, ABS, ball joint, 1.5 GPM (5.7 l/min)



Options

Suffix **V** Separate volume control, lever adjustment

Suffix **CFL** Cast flange with set screw

Diverter Spouts, Tub Spouts

All diverter and tub spouts are chrome-plated

D diverter spout



TS tub spout



D-1 diverter spout, twin elbow



Options

Suffix **BR** Brass construction (D, D-1)

Diverter Valves

D-2L inline diverter valve, brass lever handle, 1/2" copper tube connections



L-4923 shower head diverter, chrome-plated finish



Institutional Shower Heads

All institutional shower heads are polished chrome-plated and mounted on an institutional shower head bracket

H-06 institutional shower head, brass, vandal-resistant screws, 2.5 GPM (9.5 l/min)



H-06-1.5 institutional shower head, brass, vandal-resistant screws, 1.5 GPM (5.7 l/min)



H-06-ADJ institutional shower head, brass, adjustable spray with lockable setting, vandal-resistant screws, 2.5 GPM (9.5 l/min)



H-06-C10-2S institutional shower head, brass, ball joint, vandal-resistant screws, 2.0 GPM (7.6 l/min)



H-07 institutional shower head, large size, brass, ball joint, adjustable spray, vandal-resistant screws, 2.5 GPM (9.5 l/min)



H-08 institutional shower head, brass, ball joint, adjustable spray, vandal-resistant screws, 2.5 GPM (9.5 l/min)



H-09 institutional shower head, ABS, ball joint, adjustable spray, vandal-resistant screws, 2.5 GPM (9.5 l/min)



H-10 institutional shower head, brass, ball joint, volume control, vandal-resistant screws, 2.5 GPM (9.5 l/min)



H-15 Low Flow institutional shower head, brass ball joint, vandal resistant screws, 1.5 GPM (5.7 l/min)



Hand Showers

All hand showers include spray, 2.5 GPM (9.5 l/min) flow rate, 69" (1753 mm) chrome hose, double check valve, supply elbow and flange

500P with two wall hooks



501P with 24" (610mm) slide bar



501P(G) with 24" (610mm) glide rail



501P(G)-30 with 30" (762mm) glide rail



503P with 48" (1219mm) slide bar



62001 ADA-compliant hand shower with 24" grab bar



62003 ADA-compliant hand shower with 36" grab bar



Add -1.5 for 1.5 GPM option

Options:

Suffix ADJ	Deluxe adjustable spray head
Suffix QD	Quick connector fitting
Suffix 505P	Same as 500P, except 1.5 GPM hand shower
Suffix 515P	Same as 501P, except 1.5 GPM hand shower
Suffix 515P(G)	Same as 501P(G), except 1.5 GPM hand shower
Suffix 515P(G)-30	Same as 501P(G)-30, except 1.5 GPM hand shower

On/Off Valves, Metering Valve

770 compression-type volume/on/off valve, four-arm handle, exposed parts chrome-plated, 1/2" IPS connections



770-BL compression-type volume/on/off valve, blade handle



LV477B-3 metering valve, concealed, pushbutton activation, fixed cycle, 30 seconds, inlet stop, exposed parts chrome-plated, 1/2" IPS connections



Dial Thermometers

37C20A range: 20-240°F, 5-115°C, 1.12" bulb, 3-1/2" black dial, bi-metal type



37C30A range: 0-140°F, -20-60°C, 15/16" bulb, 3 color, 3-1/2" dial, bi-metal type



37C50FL flush mounted, range: 25-125°F, 0-50°C, with wall flange, mounting bracket and screws



2122 for tepid applications range: 0-140°F, -20-60°C, 15/16" bulb, special 4 color, 3-1/2" dial, bi-metal type



Accessories

Institutional Sprays

All institutional sprays include 6 ft. (1828mm) black rubber hose and wall hook

5P plain (open) end hose



5RS rose spray



5SCRS self-closing rose spray



Vacuum Breakers

LVB elevated vacuum breaker, chrome-plated, 1/2" with hose connection on outlet



EVB elevated vacuum breaker unit, chrome-plated, 1/2" IPS



INVB inline vacuum breaker



Remodel Plates

2000 remodel plate, stainless steel, #4 finish for 4500 or PAM-II-ST shower valves



7929 remodel plate, stainless steel, #4 finish for 7600 shower valve



Note: All specifications are subject to change without notice!



1360 Elmwood Avenue
Cranston, RI 02910 USA
800.222.1208
t 401.461.1200
f 401.941.5310
info@leonardvalve.com
www.leonardvalve.com

LV-113 03/15
©2015 Leonard Valve Company. Printed in the U.S.A.