

Location: _____



MIFAB®

F1350-Y-36

GARBAGE CAN WASH FLOOR DRAIN


Specification: MIFAB Series F1350-Y-36 lacquered cast iron garbage can wash floor drain with anchor flange, weepholes, and extra deep sump body with 1/2" (13) spray nozzle assembly, sediment bucket and standard 1" (25) thick, 12" (305) round, (specify material finish) tractor grate.

Function: Used in kitchens and other areas where the inside of garbage cans needs to be washed. The internal sediment bucket prevents solid and debris from entering the drain line. 12" Round, adjustable tractor grate is used with all types of poured finished floors. Deep sump body provides capacity for heavy water flow.


PARTS:



A3 Body



F1340-TA-(*)
(*) Denotes Strainer
Finish (-1, -3 or -4)



F1350-Y-36 Series
meets ANSI/ASME
floor drain standard
A112.6.3-2001

STRAINER DIAMETER	STRAINER ADJUSTMENT		ANSI/ASME RATING		PIPE SIZE	BODY HEIGHT				
	MIN	MAX	FREE AREA	LOAD RATING N.B. (-1) / S.S. (-3) / D.I. (-4)		NO HUB (STANDARD)	PUSH ON (P)	THREADED (T)	INSIDE CAULK (X)	PVC/ABS (-30)/(-31)
12" (305)	2 1/4" (57)	4 1/8" (105)	33 in ² (21,290 ²)	ANSI/ASME LOAD CLASS "SPECIAL DUTY" (OVER 10,000 LBS.)	2" (51) 3" (76) 4" (102) 5" (127) 6" (152)	12 1/4" (311) 12 1/4" (311) 12 1/4" (311) 12 1/4" (311) 12 1/4" (311)	12 1/2" (318) 12 1/2" (318) 12 1/2" (318) — 12 1/2" (318)	11 1/2" (292) 11 7/8" (302) 11 7/8" (302) 11 7/8" (302) —	13" (330) 13" (330) 13" (330) 16" (406) —	12 1/8" (308) 12 5/8" (321) 12 5/8" (321) — —

SUFFIX OPTIONAL VARIATIONS:

- 1 Nickel bronze (veneer)
- 3 Stainless steel (veneer)
- 4 Ductile iron grate
- 6 Security screws (TR30 Torx & pin)
- 7 1/2" trap seal primer connection
- 8 Backwater valve (2", 3", 4")
- 11 Acid resistant epoxy coated body
- 12 Galvanized top assembly
- 13 Galvanized body
- 15 Extension
- 16 Square top

SUFFIX

- 28 Stainless steel body (Type 304)
- 30 PVC socket connection body
- 31 ABS socket connection body
- 32 2", 3", 4" integral deep seal trap
- 34 Closure plug
- 35 Stainless steel mesh over bucket
- 40 Underdeck clamp
- 41 Sump receiver
- 90 Threaded side outlet (2", 3", 4") (cast iron only)
- 90NH No hub side outlet (2", 3", 4") (cast iron only)
- 95 Client logo

SUFFIX

- ARRA ARRA (Stimulus Act) compliant product
- BA Buy American Act compliant product
- C Membrane clamp
- HP Heel proof grate (1/4" maximum grate opening size, -3 only)
- (Standard) No hub outlet
- P Push on outlet
- PA Pennsylvania Steel Act compliant product
- T Threaded outlet (2", 3", 4")
- X Inside caulk outlet
- Z Extended wide elastomeric flange

Job Name: _____
Section No: _____
Schedule No: _____

Page No: _____
Contractor: _____
Purchase Order No: _____

MIFAB reserves the right to make changes in material and design without formal notice and obligation.

USA: 1-800-465-2736 www.mifab.com CAN: 1-800-387-3880